

BBC-13X Sound Curtains

Sound Seal's **BBC-13X** offers the benefits of both a noise barrier and a sound absorber for outdoor applications. The BBC-13X consists of a one-inch thick vinyl-coated-fiberglass-cloth faced quilted fiberglass that is bonded to a one-pound per sq. ft. reinforced loaded vinyl noise barrier. "X" style Sound Curtain panels are constructed with grommets across the top and **bottom, and exterior grade** Velcro seals along the vertical edges. The product is also available in roll form with edges bound or unbound.

- Class A (or 1) flammability rated per ASTM E 84
- For use on Indoor or Outdoor Applications
- Available facing colors: gray, tan, black, or off-white
- Available barrier colors: gray, tan, blue or olive drab



Applications:

With a minimum life span of 5 years* in the harshest environments, this product is typically used as a **temporary noise barrier on outdoor applications such as construction site noise mitigation projects**. Also available with a two-pound psf noise barrier or a two-inch thick quilted fiberglass sound absorber for better acoustical performance.

Product Data:

Description	Vinyl coated fiberglass cloth facing on 1" quilted fiberglass 1lb-psf reinforced loaded vinyl barrier
Flammability	Flame Spread: 23.0 Smoke density: 30.0
Nominal thickness	1.0 inch
Temperature range	-20° to +180° F
Standard roll size	54" wide x 25' long
Weight	1.2 lb psf

Acoustical Performance:

Sound Transmission Loss

Product	OCTAVE BAND FREQUENCIES (Hz)						STC
	125	250	500	1000	2000	4000	
BBC-13 X	11	16	24	30	35	35	27

ASTM E-90 & E 413

Sound Absorption Data

Product	OCTAVE BAND FREQUENCIES (Hz)						NRC
	125	250	500	1000	2000	4000	
BBC-13 X	.12	.47	.85	.84	.64	.62	.70

ASTM C 423

* when properly installed.



QUALITY YOU CAN HEAR
 2677 N. Main Street, Suite 230, Santa Ana, CA 92705
 (714) 892-6022 MAIN (714) 892-3155 FAX

Quotation

To: Menlo Circus Club
 For: Pickle Ball Noise Mitigation
 Quoting: **Sound Seal Acoustic panels**

DATE 8/30/2023
Quotation # 30830-2673

This quote is valid for 60 days. Payment terms are net 30 days. Lead time will be approx 4-5 weeks (after submittal approval)+ plus shipping time. Addendums through Addm# **** none **** are noted and included.

Quantity	Description	Each	Price
56	<p>Sound Seal Panels consist of 1lb/psf vinyl noise barrier and 2" thick exterior grade vinyl faced quilted fiberglass absorber.</p> <p>BBC13X panels are fabricated with Gore-Tenara thread, grommets along top, middle & bottom with 2" mating vertical Velcro seals. Black in color.</p> <p>Panels are 54" wide x 108" tall and will cover a height of 9' over 250 LF.</p> <p>NRC 0.70 and STC 27.</p> <p>Price includes material, freight and tax.</p>		
***** (Options below are not included in total price) *****			
Option 1			
Option 2			
Option 3			
Notes	<p>CE Pickup Company, Inc. - CSLB # 647465, DIR Registration #1000007590 This quote is subject to a 25% cancellation fee if cancelled after being accepted in any form. Quotation is for material only, no install included - Freight included Cost of dumpster NIC, permits, fees, structural engineering not included unless noted above.</p>		
8.50%	State sales tax - San Francisco County, CA	Included	
Visa, Amex, MC payment available with 3% CC processing fee paid by client		Total	\$29,923

Please call with any questions 480-205-3752 or email J.

Pacific Sound Control , a CE Pickup Company

Jeff Bootz

Jeff Bootz
 Applications Engineer